

# BIGFOOT 15

90 DAYS UV EXPOSURE

## TECHNICAL SPECIFICATIONS

SPECIFICATIONS	PARAMETER
ROLL LENGTH	250'
ROLL WIDTHROLL	48"
ROLL COVERAGE	10 SQ
ROLL WEIGHT	19 LBS
ROLLS/PALLET	72
PALLET WEIGHT	1368 LBS
UV EXPOSURE GUARANTEE	90 DAYS
LIMITED WARRANTY	25 YRS

**BIGFOOT 15** IS DESIGNED FOR USE UNDER MECHANICALLY ATTACHED ASPHALT SHINGLES, METAL ROOFING AND TILE, REPLACE OF 15# OR 30# FELT

## FEATURES AND ADVANTAGES

- ★ **Strong:** 25X stronger than 15# felt and 30# felt, 6X lighter than 15# felt and 30# felt. Provides tough durable weather and tear resistance.
- ★ **Gripwalk:** Unique gray surface offering superior foot traction, and more friction and slip resistance than standard roofing felt.
- ★ **Easy to Handle:** Lighter weight rolls for easy handling during all stages of installation.
- ★ **Simple to Apply:** Installs quick and easy, provides 17% more coverage per course than a standard roll of 15# felt and 30# felt.
- ★ **Reliable:** Highly water-repellent, reduces warping, wrinkling, and cracking in cold weather.
- ★ **100% Recyclable:** 100% inorganic, will not rot or mold, considered a Green Building Product. Price is competitive with 15# felt and 30# felt.
- ★ **Cool Gray:** Unique gray high-traction top layer which reduces heat and provides a cooler working surface.
- ★ **Skid-Resistant:** Anti-slip coating added to enhance the skid-resistant properties of the synthetic roofing underlayment, protecting against costly slips and falls.

## TESTING | CERTIFICATIONS

ICC-ESR 5197

FLORIDA FBC#FL 42105

ASTM E108 CLASS A

ASTM D226 AND ASTM D8257

AC 188 AND CAN/CSA A123.3

TEXAS DEPARTMENT OF INSURANCE

RANGE OF TEMPERATURE -40°F TO 240°F



**MOUNTAIN  
BIGFOOT  
BARRIER™**  
RARELY SEEN, ALWAYS THERE

**LET'S MAKE ROOFING BETTER TOGETHER**  
[WWW.AMERICANBP.COM](http://WWW.AMERICANBP.COM)