

## **TECHNICAL SPECIFIATIONS**

SPECIFICATIONS	PARAMETER
ROLL LENGTH	250'
ROLL WIDTHROLL	48''
ROLL COVERAGE	10 SQ
ROLL WEIGHT	26 LBS
ROLLS/PALLET	56
PALLET WEIGHT	1456 LBS
UV EXPOSURE GUARANTEE	180 DAYS
LIMMITED WARRANTY	40 YRS

**BIGFOOT 180** IS DESIGNED FOR USE UNDER MECHANICALLY ATTACHED ASPHALT SHINGLES, METAL ROOFING AND TILE, SLATE, REPLACE OF 15# OR 30# FELT



## FEATURES AND ADVANTAGES

- **Strong:** 25X stronger than 30# felt, 10X lighter than 30# felt. Provides tough durable weather and tear resistance.
- ★ **Gripwalk:** Unique gray surface offering superior foot traction, and more friction and slip resistance than standard roofing felt.
- **Easy to Handle:** Lighter weight rolls for easy handling during all stages of installation.
- Simple to Apply: Installs quick and easy, provides 17% more coverage per course than a standard roll of 30# felt.
- \* **Reliable:** Highly water-repellent, reduces warping, wrinkling, and cracking in cold weather.
- \* 100% Recyclable: 100% inorganic, will not rot or mold, considered a Green Building Product. Price is competitive with 30# felt.
- Cool Gray: Unique gray high-traction top layer which reduces heat and provides a cooler working surface.
- Skid-Resistant: Anti-slip coating added to enhance the skid-resistant properties of the synthetic roofing underlayment, protecting against costly slips and falls.

## **TESTING | CERTIFICATIONS**

**ES ICC-ESR 5197** 

FLORIDA FBC#FL 42105

ASTM E108 CLASS A


ASTM D226 AND ASTM D8257

AC 188 AND CAN/CSA A123.3

TEXAS DEPARTMENT OF INSURANCE

RANGE OF TEMPERATURE -40°F TO 240°F













**BIGFOOT 180 BARRIER** WARRANTY

LET'S MAKE ROOFING BETTER TOGETHER WWW.AMERICANBP.COM