

BIGFOOT^{HD}

365 DAYS UV EXPOSURE

TECHNICAL SPECIFICATIONS

SPECIFICATIONS	PARAMETER
ROLL LENGTH	250'
ROLL WIDTHROLL	48"
ROLL COVERAGE	10 SQ
ROLL WEIGHT	38 LBS
ROLLS/PALLET	30
PALLET WEIGHT	1140 LBS
UV EXPOSURE GUARANTEE	365 DAYS
LIMITED WARRANTY	50 YRS

BIGFOOT HD IS DESIGNED FOR USE UNDER MECHANICALLY ATTACHED ASPHALT SHINGLES, METAL ROOFING AND TILE, SLATE, CONCRETE & CLAY TILES, REPLACE OF 15# OR 30# FELT

FEATURES AND ADVANTAGES

- ★ **Strong:** 35X stronger than 30# felt, 8X lighter than 30# felt. Provides tough durable weather and tear resistance.
- ★ **Gripwalk:** Unique gray surface offering superior foot traction, and more friction and slip resistance than standard roofing felt.
- ★ **Easy to Handle:** Lighter weight rolls for easy handling during all stages of installation.
- ★ **Simple to Apply:** Installs quick and easy, provides 17% more coverage per course than a standard roll of 30# felt.
- ★ **Reliable:** Highly water-repellent, reduces warping, wrinkling, and cracking in cold weather.
- ★ **100% Recyclable:** 100% inorganic, will not rot or mold, considered a Green Building Product. Price is competitive with 30# felt.
- ★ **Cool Gray:** Unique gray high-traction top layer which reduces heat and provides a cooler working surface.
- ★ **Skid-Resistant:** Anti-slip coating added to enhance the skid-resistant properties of the synthetic roofing underlayment, protecting against costly slips and falls.

TESTING | CERTIFICATIONS

ICC-ESR 5197

FLORIDA FBC#FL 42105

ASTM E108 CLASS A

ASTM D226 AND ASTM D8257

AC 188 AND CAN/CSA A123.3

TEXAS DEPARTMENT OF INSURANCE

RANGE OF TEMPERATURE -40°F TO 240°F



LET'S MAKE ROOFING BETTER TOGETHER
WWW.AMERICANBP.COM